



Unica

Inserts

Comfort devices

Dimmers

	Universal	Compensation module LED
2-module		
		
☐ white	NU351418	—
☐ aluminium	NU351430	—
☐ anthracite	NU351454	—
Load compensation module		
	—	CCT90501
Maximum loads		
LED lamp 230 V 	RC: 5...100 VA RL: 5...20 VA	
incandescent lamp 230 V 	5...200 W	
halogen lamp 230 V 	5...150 W	
LV halogen lamps 12 V  electronic transformer	5...150 VA	
 wound transformer	5...150 VA	
Characteristics		
• Remote control by unlimited number of auxiliary push-button • Automatic load detection • Wire configuration without neutral • Screw terminals connection • Memory function • Automatic overload protection, overheating protection, short-circuit protection		• Rated voltage: 230 V AC • Frequency range: 50 - 60 Hz • Power loss: 2 W max. • Installation: junction box, in the luminaire or in the sub-distribution panel, wired between neutral and dimmed phase.

Thermostats

	Room – 8 A	Floor – 10 A
2-module		
		
☐ white	NU350118	NU350318
☐ aluminium	NU350130	NU350330
☐ beige	NU350144	NU350344
☐ anthracite	NU350154	NU350354
Characteristics		
	• For heating or air-conditioning • Settings range: + 5 to + 30 °C • Blue and red LED's for conditioning or heating indication	• For floor heating • Settings range: + 5 to + 45 °C • Green LED for voltage supply indication • Red LED for heating indication • Delivered with a 4 m temperature sensor