

SBLUX INACTINIC



STANDARDS



OPTIONS



FR



Données mécaniques

Montage: Encastré par dessus sur les faux plafonds modulaires ou par le dessous selon la demande
Ouverture du luminaire par le dessus
Corps: tôle d'acier électrozinguée
Finition peinture: époxy blanc



Données électriques

Source lumineuse : modules LED intégrés
Alimentation : 220-240V 50-60 Hz
Équipement : Driver LED
Durée de vie : 50 000h L 80/B10 (ta 25°C)



Données optiques

Modèle d'éclairage : Direct
Répartition de la lumière : Symétrique
Diffuseur : Vasque opale
Couleur : blanc, amber, rouge



Données complémentaires

Application : Domaine hospitalier, Industrie pharmaceutique, Laboratoires
H₂O₂ résistance



Accessoires (en option)

Filin de sécurité
Presse étoupe PG 13.5 (diamètre de câble 6-12mm)
Connecteur IP68

EN

Mechanical data

Mounting: Recessed from above on modular false ceilings or from below as required
the luminaire opens from above
Body: electro-galvanized steel sheet.
Paint finish: White epoxy

Electrical data

Light source: integrated LED modules
Power supply: 220-240V 50-60 Hz
Equipment: LED driver
Lifespan: 50,000h L 80 / B10 at 50 ° C

Optical data

Lighting model: Direct
Light distribution: Symmetrical
Optical system: Opal diffuser
Color: white, amber, red


Additional data

Application: Hospitals, Pharmaceutical industry, Laboratories
H₂O₂ resistance

Accessories (optional)

Security steel cable
PG 13.5 cable gland (cable diameter 6-12mm)
IP68 connector

ARTICLE	 (mm)	 (mm)	 (mm)	A	B
SBLUX INA 60*30	595	295	100	580	288
SBLUX INA 60*60	595	595	100	580	580
SBLUX INA 120*30	1195	295	100	1180	280



Articles	code	Lm/Output	W	Lm/W	CCT	
SBLUX INA RED 60x60 36W	PF2LULED407	1728	36	48	RED	8,3 KG
SBLUX INA AMBER 60x60 50W	PF2LULED408	4950	50	99	AMBER	8,3 KG
SBLUX INA WHITE/RED 60x60 52/36W	PF2LULED409	4888/1728	52/36	94/48	6500K/RED	8,3 KG
SBLUX INA WHITE/AMBER 60*60 52/50W	PF2LULED410	4888/4950	52/50	94/99	6500K/AMBER	8,3 KG
SBLUX INA RED 120x30 36W	PF2LULED411	1728	36	48	RED	8,3 KG
SBLUX INA AMBER 120x30 50W	PF2LULED412	4950	50	99	AMBER	8,3 KG
SBLUX INA WHITE/RED 120x30 52/36W	PF2LULED413	4888/1728	52/36	94/48	6500K/RED	8,3 KG
SBLUX INA WHITE/AMBER 120x30 52/50W	PF2LULED414	4888/4950	52/50	94/99	6500K/AMBER	8,3 KG