

TUBALUX LED 360



STANDARDS



FR



Données mécaniques

Montage : suspendu verticalement ou horizontalement et raccordement par presse-étoupe étanche.

Corps : Platine interne en tôle d'acier laqué blanc et embouts inox (autres couleurs sur demande)



Données électriques

Source lumineuse : Modules LED intégrés

Alimentation : 220-240V 50-60 Hz

Équipement : Driver LED (Déporté longueur du fil maximale 2m)

Durée de vie : 50 000h L 80/B10 à 50°C



Données optiques

Diffuseur : Fourreau polycarbonate opale d'épaisseur 2 mm



Données complémentaires

Étrier inox

Filin de suspension

OPTIONS



EN

Mechanical data

Mounting: suspended vertically or horizontally and connection by waterproof cable gland

Body: Internal plate in white lacquered steel sheet and stainless steel end-caps (other colors on request)

Electrical data

Light source: integrated LED modules

Power supply: 220-240V 50-60 Hz

Equipment: LED driver (Offset maximum wire length 2m)

Lifespan: 50,000h L 80 / B10 at 50 °C

Optical data


Diffuser: 2 mm thick opal polycarbonate tube

Additional data

Stainless steel bracket

Suspension rope

ARTICLE	 (mm)	 (mm)
TUBALUX 360° 600	640 mm	80 mm
TUBALUX 360° 900	980 mm	80 mm
TUBALUX 360° 1200	1240 mm	80 mm



Articles	code	Lm/Output	W	Lm/W	CCT			
TUBALUX OP 360° 600 28W 3K	PFOLULED293	2240	28	80	3000K	N/A	1	50
TUBALUX OP 360° 600 28W 4K	PFOLULED294	2352	28	84	4000K	N/A	1	50
TUBALUX OP 360° 600 28W 6,5K	PFOLULED295	2408	28	86	6500K	N/A	1	50
TUBALUX OP 360° 900 41W 3K	PFOLULED296	3280	41	80	3000K	N/A	1	50
TUBALUX OP 360° 900 41W 4K	PFOLULED297	3444	41	84	4000K	N/A	1	50
TUBALUX OP 360° 900 41W 6,5K	PFOLULED298	3526	41	86	6500K	N/A	1	50
TUBALUX OP 360° 1200 54W 3K	PFOLULED299	4320	54	80	3000K	N/A	1	50
TUBALUX OP 360° 1200 54W 4K	PFOLULED300	4536	54	84	4000K	N/A	1	50
TUBALUX OP 360° 1200 54W 6,5K	PFOLULED301	4644	54	86	6500K	N/A	1	50

