

SBLUX LED OP



STANDARDS



OPTIONS



FR



Données mécaniques

Montage: Encastré par dessus sur les faux plafonds modulaires ou par le dessous selon la demande
Ouverture du luminaire par le dessus ou par le dessous selon la demande
Corps: tôle d'acier électrozinguée
Finition peinture: époxy blanc



Données électriques

Source lumineuse : modules LED intégrés
Alimentation : 220-240V 50-60 Hz
Équipement : Driver LED
Durée de vie : 50 000h L 80/B10 (ta 25°C)



Données optiques

Modèle d'éclairage : Direct
Répartition de la lumière : Symétrique
Diffuseur: Vasque opale



Données complémentaires

Application : Domaine hospitalier, Industrie pharmaceutique, Laboratoires
H₂O₂ résistance



Accessoires (en option)

Filin de sécurité
Presse-étoupe PG 13.5 (diamètre de câble 6-12mm)
Connecteur IP68

EN

Mechanical data

Mounting: Recessed from above on modular false ceilings or from below as required
Opening of the luminaire from above or below depending on the request
the luminaire opens from above
Body: electro-galvanized steel sheet.
Paint finish: White epoxy

Electrical data

Light source: integrated LED modules
Power supply: 220-240V 50-60 Hz
Equipment: LED driver
Lifespan: 50,000h L 80 / B10 at 50 ° C

Optical data

Lighting model: Direct
Light distribution: Symmetrical
Optical system: Opal diffuser

Additional data

Application: Hospitals, Pharmaceutical industry, Laboratories
H₂O₂ resistance


Accessories (optional)

Security steel cable
PG 13.5 cable gland (cable diameter 6-12mm)
IP68 connector

ARTICLE



SBLUX LED OP 60*30	595	295	85
SBLUX LED OP 60*60	595	595	85
SBLUX LED OP 120*30	1195	295	85



Articles

code

Lm/Output

W

Lm/W

CCT



SBLUX OP 60x30 16 W 3K	PF0LULED776	1792	16	112	3000K	4,7 KG	1	50
SBLUX OP 60x30 16 W 4K	PF0LULED777	1920	16	120	4000K	4,7 KG	1	50
SBLUX OP 60x30 16 W 6.5K	PF0LULED778	1952	16	122	6500K	4,7 KG	1	50
SBLUX OP 60x60 32 W 3K	PF0LULED779	3584	32	112	3000K	8,3 KG	1	50
SBLUX OP 60x60 32 W 4K	PF0LULED780	3840	32	120	4000K	8,3 KG	1	50
SBLUX OP 60x60 32 W 6.5K	PF0LULED781	3904	32	122	6500K	8,3 KG	1	50
SBLUX OP 120x30 32 W 3K	PF0LULED782	3584	32	112	3000K	8,3 KG	1	50
SBLUX OP 120x30 32 W 4K	PF0LULED783	3840	32	120	4000K	8,3 KG	1	50
SBLUX OP 120x30 32 W 6.5K	PF0LULED784	3904	32	122	6500K	8,3 KG	1	50

