


Tôle nervurée TN 35 — 4 nervures

PANNEAUX DU MAGHREB • TN 35



Tôle d’acier galvanisé prélaqué pour couverture sèche et bardage vertical, disponible en plusieurs épaisseurs.

Couverture sèche • Bardage vertical • Hangars et bâtiments agricoles

Visuel de gamme. Configuration à confirmer au devis.

CARACTÉRISTIQUES

Nombre de nervures	4
Hauteur du profil dessinée	35 mm
Largeur utile	1 000 mm
Longueur	2 à 12 m
Métal	Acier galvanisé prélaqué
Épaisseurs standards indiquées	0,50 / 0,63 / 0,75 mm
Nuances mentionnées	S250, S280, S320, DX51D
Coloris présentés	RAL 9010, 9002, 9007, 6017, 5015, 1016, 3020

VARIANTES ET OPTIONS

0.50 mm	Épaisseur de tôle à sélectionner selon étude
0.63 mm	Épaisseur de tôle à sélectionner selon étude
0.75 mm	Épaisseur de tôle à sélectionner selon étude


POUR VOTRE PROJET

Indiquer les dimensions du bâtiment, les longueurs de tôles, l’épaisseur, le coloris, l’entraxe des supports et les charges. Prévoir les recouvrements et les accessoires de fixation.

Synthèse des données de gamme publiées par le fabricant. Dimensions, finitions et configuration finale selon offre. Les valeurs thermiques indiquées se rapportent aux épaisseurs documentées.

TN 35 profiled steel sheet — 4 ribs

PANNEAUX DU MAGHREB • TN 35



Prepainted galvanised steel sheet for single-skin roofing and vertical cladding, available in several thicknesses.

Single-skin roofing • Vertical cladding • Warehouses and agricultural buildings

Range image. Final configuration confirmed in the quotation.

SPECIFICATIONS

Number of ribs	4
Profile height shown	35 mm
Effective width	1 000 mm
Length	2 to 12 m
Metal	Prepainted galvanised steel
Listed standard thicknesses	0.50 / 0.63 / 0.75 mm
Listed steel grades	S250, S280, S320, DX51D
Listed colours	RAL 9010, 9002, 9007, 6017, 5015, 1016, 3020

VARIANTS AND OPTIONS

0.50 mm	Select sheet thickness according to design
0.63 mm	Select sheet thickness according to design
0.75 mm	Select sheet thickness according to design

FOR YOUR PROJECT

Provide building dimensions, sheet lengths, thickness, colour, support spacing and loads. Allow for overlaps and fixing accessories.

Summary of published manufacturer range data. Dimensions, finishes and final configuration are specified in the quotation. Thermal values refer to the documented thicknesses.